



承 认 书

APPROVAL SHEET

客 户:

CUSTOMER: _____

品 名:

PARTNAME: _____ 铝电解电容器(E-CAP)

系 列:

SERIES: _____ CD50(MS)系列

规 格:

SPECIFICATION: _____ 见尺寸表

版本号:

VERSION: _____ QWH-15.001

日 期:

DATE: _____ 2015.01.01

制 造 MANUFACTURE		客 户 CUSTOMER	
拟 制 FORMULATE	批 准 APPROVAL	检 验 CHECK	批 准 APPROVAL
郭嘉敏	技术部 郭嘉敏		

[illegible]



序号 No	目 录 INDEX	页 page
1	概述 SCOPE	4
2	订货方式 HOW TO ORDER	4
3	主要特性表 MAIN SPECIFICATIONS	5
4	外形尺寸图 SHAPE AND DIMENSIONS	6
5	纹波电流频率因子 RIPPLE CURRENT FREQUENCY COEFFICIENT	7
6	尺寸表、允许纹波电流 DIMENSIONS AND RIPPLE CURRENT	8
7	包装 PACKING	9
8	贮存方法 STORAGE METHODS	9
9	其他说明 OTHERS	10

1. 概述 SCOPE

1.1 概述 SCOPE

本承认书规定了铝电解电容器的技术规范。

This specification contains descriptions of the quality of aluminum electrolytic capacitors.

1.2 参考标准 APPLICABLE SPECIFICATION

本承认书参考 JISC-5141 和 JISC-5102 制定。

This specification is made based on the Japanese Industrial Standard JISC-5141 Characteristics and JIS C-5102.

1.3 工作温度范围 OPERATING TEMPERATURE RANGE

工作温度范围是电容器在施加额定工作电压条件下,可以长期可靠工作的环境温度范围。

Operating temperature range is the range of ambient temperature at which the capacitor can be operated continuously at rated voltage.

2. 订货方式 HOW TO ORDER

2.1 订货方式 HOW TO ORDER

The diagram illustrates the 10-digit EIA-188C marking code structure. The digits are grouped into 10 positions, each with a specific meaning. The diagram shows the mapping from the digit to its meaning and the corresponding table for that meaning.

Position 1: 8 (Code 8) - 产品类别 (Product Type)

代码 Code	产品类别 Type
8	成品 Product
1	素子 Element
2	裸品 Semifinished Product

Position 2: 2 (Code 2) - 标称容量 (Nominal Capacitance)

代码 Code	标称容量 Nominal Capacitance
R22	0.22uF
1R0	1uF
2R2	2.2uF
220	22uF
221	220uF

Position 3: L (Code L) - 电压 (Voltage)

代码 Code	电压 Voltage
LO	4
LA	6.3
LB	10
LC	16
LD	25
LE	35
LF	50

Position 4: M (Code M) - 误差 (Tolerance)

代码 Code	误差 Tolerance
J	±5%
K	±10%
V	± ²⁰ ₁₀ %
M	±20%
Q	± ³⁰ ₁₀ %
T	± ⁵⁰ ₁₀ %
A	特殊

Position 5: 0 (Code 0) - 尺寸 (Dimensions)

代码 Code	尺寸 Dimensions
0405	Φ4x5.5Type
0505	Φ5x5.5Type
AA05	Φ6.3x5.5Type
AA07	Φ6.3x7.7Type

Position 6: M (Code M) - 型号 (Series)

代码 Code	型号 Series
MS	CD50

Position 7: 0 (Code 0) - 商标 (Trademark)

代码 Code	商标 Trademark
0	无商标
N	LH.NOVA

Position 8: 0 (Code 0) - 胶管颜色 (Sleeve Color)

代码 Code	胶管颜色 Sleeve Color
0	黑色 Black

Position 9: 0 (Code 0) - 内码 (Internal Code)


代码 Code	内码 Internal Code
01	贴片品

Position 10: T (Code T) - 产品脚型 (Lead Forming Type)

代码 Code	产品脚型 Lead Forming Type
0	散装品 Bulk
T	5mm 贴片编带品 5mm Chip tape

项目 Item	主要特性 Performance Characteristics
高温负荷特性 Load life	在+85℃ 环境中施加额定工作电压和最大允许纹波电流 2000 小时后,电容器的性能符合下面要求: After application of rated working voltage with max permissible ripple current specified at +85℃ for 2000 hours, capacitors meet the characteristics requirements measured at +20℃ listed at below: 1、电容量变化率:±25%初始测量值以内 Capacitance change : ±25% initial measured value 2、漏电流: ≤初始规定值 Leakage current:≤initial specified value 3、损耗角正切值≤200%倍初始规定值 Dissipation factor: ≤200% initial specified value
高温贮存特性 Shelf life	在+85℃环境无负荷放置 1000 小时后,电容器的性能符合高温负荷特性中所列的规定值 After leaving capacitors under no load at +85℃for 1000 hours, capacitors meet the characteristics listed above.
耐焊接热试验 Test of resistance to soldering heat	电容引脚向下放置在一块金属板上,在 250℃下放置 30 秒,取出后放置于空气中到达室温,测试性能符合下表要求。 Capacitors placed on a 250℃ hot plat for 30 seconds with their electrode terminais facing downward will fulfill following conditions after being cooled to room temperature. 1、电容量变化率:±10%初始测量值以内 Capacitance change : ±10% initial measured value 2、漏电流: ≤初始规定值 Leakage current:≤initial specified value 3、损耗角正切值≤初始规定值 Dissipation factor: ≤initial specified value

4. 外形尺寸 SHAPE AND DIMENSIONS (mm)



ϕD	L	A	B_1	C	W_1	$P \pm 0.2$
4	5.5	4.3	4.3	1.8	0.5~0.8	1.0
5	5.5	5.3	5.3	2.1	0.5~0.8	1.4
6.3	5.5	6.6	6.6	2.5	0.5~0.8	2.0
6.3	7.7	6.6	6.6	2.5	0.5~0.8	2.0

4. 1 回流焊温度曲线 REFLOW SOLDERING CURVE OF TEMPERATURE

4. 1. 1 电容表面温度不超过 260℃

Temperature at surface of capacitor shall not exceed 260℃.


4. 1. 2 电容表面温度超过 200℃ 的时间不超过 90 秒

Period that temperature at surface of capacitor becomes more than 200℃ shall not exceed 90 seconds.


4. 1. 3 预热温度不超过 200℃，时间不超过 180 秒

Preheat shall be made at maximum 200℃ and for maximum 180 seconds.

无铅回流焊温度曲线图 Graph for Lead-free reflow sold cringe temperature



4. 2 编带 TAPING METHOD (mm)



系列 Series	尺寸 Size	W ₂	A ₂	B ₂	P	t ₂	F	t ₁
CD50 MS	φ 4×5.5	12.0	4.7	4.7	8	5.7	5.5	0.4
	φ 5×5.5	12.0	5.7	5.7	12	5.7	5.5	0.4
	φ 6.3×5.5	16.0	7.0	7.0	12	5.7	7.5	0.4
	φ 6.3×7.7	16.0	7.0	7.0	12	8.3	7.5	0.4

5. 纹波电流频率因子 RIPPLE CURRENT FREQUENCY COEFFICIENT

Freq (Hz) Cap (μF)	50 (60)	100 (120)	500	1K	≥10K
0.1~1	0.50	1.00	1.20	1.30	1.50
2.2~4.7	0.65	1.00	1.20	1.30	1.50
10~47	0.80	1.00	1.20	1.30	1.50
100~330	0.80	1.00	1.10	1.15	1.20



6. 尺寸表、允许纹波电流 DIMENSIONS AND RIPPLE CURRENT (MS)

WV/V Cap/μF	4(LO)		6.3(LA)		10(LB)		16(LC)		25(LD)		35(LE)		50(LF)	
	(1)	(2)	(1)	(2)	(1)	(2)	(1)	(2)	(1)	(2)	(1)	(2)	(1)	(2)
0.1(R10)													4×5.5	1.0
0.22(R22)													4×5.5	2.0
0.33(R33)													4×5.5	2.5
0.47(R47)													4×5.5	4.0
1(1R0)													4×5.5	8.4
2.2(2R2)													4×5.5	14
3.3(3R3)													4×5.5	17
4.7(4R7)									4×5.5	18	4×5.5	18	4×5.5 5×5.5	18 22
10(100)							4×5.5	25	4×5.5 5×5.5	25 30	5×5.5	30	5×5.5 6.3×5.5	30 35
22(220)			4×5.5	29	4×5.5	30	4×5.5 5×5.5	30 39	5×5.5	36	6.3×5.5	48	6.3×5.5	48
33(330)	4×5.5	28	4×5.5	31	4×5.5 5×5.5	32 43	5×5.5	43	6.3×5.5	54	6.3×5.5	58		
47(470)	4×5.5	34	4×5.5 5×5.5	36 46	5×5.5 6.3×5.5	46 61	5×5.5 6.3×5.5	50 60	6.3×5.5	61	6.3×7.7	61 59		
100(101)	5×5.5	61	5×5.5 6.3×5.5	61 71	5×5.5 6.3×5.5	61 71	6.3×5.5	86	6.3×7.7	91	6.3×7.7	90		
220(221)	6.3×5.5	96	6.3×5.5 6.3×7.7	105 110	6.3×5.5 6.3×7.7	105 130	6.3×7.7	135						
330(331)	6.3×7.7	130	6.3×7.7	150										
470(471)	6.3×7.7	150												

(1) 外形尺寸 Case Size D×L(mm)

(2) 最大允许纹波电流 Max allowable ripple current (mA rms +85℃,120Hz)

6.1 客户料号与风华物料对照表 Customer P/N and Fenghua P/N collate list

客户 P / N	风华 P / N
--	

7. 包装 PACKING

7.1 包装标签 PACKING LABEL

规格、尺寸
Specification and dimensions

品名 PRODUCT: 铝电解电容器 E-CAP
 编码 CODE: _____
 批号 LOT: _____
 数量 QTY: _____

CP
 RoHS
 RoHS
 RoHS


Fenghua Advanced Technology (Holding) Co., Ltd.

批号的填写 LOT:

1	2	3	4	5	6	7	8	9	10	11	12	13	14
类别	年份	月份	日期	区别号			流传单号码						
Sort	Year	Month	Date	Discriminate mark			Sequence number						

7.2 编带产品按下图包装

Taped capacitors are packed into carton, according to the following drawing.



垂直安装 Vertical Mount			
尺寸 Size	L	W ₃	数量 Quantity/reel
Φ4×5.5	19	14	2000pcs
Φ5×5.5	19	14	1000pcs
Φ6.3×5.5	23	18	1000pcs
Φ6.3×7.7	23	18	1000pcs

7.3 散装、编带品外包装箱不干胶标签，实用尺寸为 167.5mmX97.5mm。

The dimension of the label on the carton is 167.5mmX97.5mm

客户 CUSTOMER: _____ 箱号: C/No.: _____
 编码 CODE: _____ 偏差 TOL.: _____
 规格 SPE: _____ μF _____ V 尺寸 SIZE: Φ _____ X _____
 数量 QTY: _____ 千只 KPCS 日期 DATE: _____
 批号 LOT: _____
 净重 NET: _____ 公斤 KG 毛重 GROSS: _____ 公斤 KG
 P/O No.: _____ 料号 P/N: _____

CP
 RoHS
 RoHS
 RoHS

Fenghua Advanced Technology (Holding) Co., Ltd.

8. 贮存方法 STORAGE METHODS

保存期限: 1 年, 如果没有其他规定, 标准的测试、检验环境条件如下所示:

环境温度: 5 至 35℃; 相对湿度: 45 至 85%; 大气压力: 86kpa 至 106kpa。

如果对测试结果有异议, 可以在以下条件测试:

环境温度: 20±2℃; 相对湿度: 60 至 70%; 大气压力: 86kpa 至 106kpa。



Storage life: 1 year, Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests are as follows.

Ambient temperature: 5 to 35°C Relative humidity: 45 to 85% Air pressure: 86kpa to 106kpa.

If there may be doubt on the results, measurements shall be made within the following limits.

Ambient temperature: 20±2°C Relative humidity: 60 to 70% Air pressure: 86kpa to 106kpa.

9. 其它说明 OTHERS

9.1 铝电解电容器使用注意事项 Important information on the application of aluminium electrolytic capacitors

(1).直流铝电解电容器应按正确的极性使用 DC electrolytic capacitors are polarized

当直流铝电解电容器被反极性接入电路时, 电容器会导致电子线路短路, 由此产生的电流会引致电容器损坏。若电路中有可能在负引线施加正极电压, 请选用无极性产品。

When reverse voltage is applied on DC electrolytic capacitor, the capacitor will become short-circuited please use non-polarized capacitors in the circuit or the capacitor will be damage due to abnormal current flows through the capacitors since the circuit where the positive voltage may be applied to the cathode terminal.

(2).在额定工作电压以下作用 Use capacitor within rated voltage

当电容器上所施加电压高于额定工作电压时, 电容器的漏电流将上升, 其电气特性将在短时期内劣化直至损坏。请注意电压峰值勿超出额定工作电压。

When capacitor is used at higher voltage than the rated voltage, leakage current increases, characteristics drastically deteriorate and damage in a short period may occur as a result. Please take extra caution that the peak voltage should not exceed the rated voltage.

(3).作快速充放电使用 Charge and discharge application.

当常规电容器被用作快速充电用途。其使用寿命可能会因为容量下降, 温度急剧上升等而缩减

When aluminum electrolytic capacitors for general purpose are employed in rapid charge and discharge application, its life may be shorted by capacitance decreasing, heat rising, etc.

(4).电容器贮存 Store the capacitor.

当铝电解电容器作了长期贮存后, 其漏电流通常升高, 贮存温度愈高, 漏电流上升愈快。因此应注意贮存环境的选择, 在电容器上施加电压后, 漏电流值将不断下降, 在铝电解电容器的漏电流值上升对电路有不良影响的, 请在使用前充电处理。

I creased leakage current is common in aluminum capacitors which have been stored for long period of time. The Higher the storage temperature, the higher the leakage current increase, therefore please take precautions concerning the storage location. The leakage current decreases gradually as voltage is applied to the capacitor. In cases where increased leakage current causes problems in the circuit, apply voltage (aging) before using.

(5).施加纹波电流应小于额定值 Ripple current applied to capacitor should not exceed the rated value.

施加纹波电流超过额定值后, 会导致电容器体过热, 容量下降, 寿命缩短。所施加纹波电压的峰值应小于额定工作电压。

Excessive heat will reduce capacitance and result in shortened life of capacitor if ripple currents exceeding the specified rated value are applied. The peak value of the ripple voltage should be less than the rated voltage.

(6).使用环境温度 Ambient temperature.

铝电解电容器的使用寿命会受到环境温度的影响。据科学统计, 使用环境温度下降 10°C 其使用寿命增加 1 倍。

Its ambient temperature closely affects the life of an aluminum electrolytic capacitor. It is generally stated, that life doubles for each 10°C decrease in temperature.

(7).引出线强度 Lead stress

当拉力施加到电容器引出线, 该拉力将作用于电容器内部, 这将导致电容器内部短路, 开路或漏电流上升。在电容器焊装到电路板, 请勿强烈摇动电容器。

When a strong force is applied to the lead wires or terminals, stress is put on the internal connections. This may result in short circuit, open circuit or increased leakage current. It is not advisable to bend or handle a capacitor after it has been soldered to the PCB board.

(8).焊接过程耐热性 Heat resistance at the soldering process

铝电解电容器装至电路板进行浸焊或波峰焊时, 其塑料套管可能因焊接时间过长、温度过高而发生破裂或二次收缩。

In the dip soldering process of PCB board with aluminum electrolytic capacitors mounted, secondary shrinkage or crack of PVC sleeve may be observed when solder temperature is too high or dipping time is too long.

(9).电路板的安装孔距及安装位置 Hole pitch and position of PCB board.

电路板安装孔的设计应与产品说明书的引线脚距相一致, 如果将电容器强行插入孔距不配套的电路板, 那么会有应力作用于引出线, 这将导致短路或漏电流上升。

PCB board must be designed so its hole coincides with the lead pitch (lead spacing) of the capacitor specified by the catalog or specifications. When a capacitor is forcibly inserted into an unmatched hole, a stress is put on the leads. This could result in a short circuit or increased leakage current.

9.2 本产品不含铅、镉等元素 This product does not include Plumbum or Cadmium.